Hurricane

TRIPLE MOTOR WET/ DRY INDUSTRIAL VACUUM



Key Features:

- Tangential suction inlet with integrated separation cyclone
- Three powerful by pass motors with independent cooling
- Durable steel construction
- Compact and mobile
- External Filter Shaker
- Filtration and recovery of cutting oil and coolant
- Unique integrated tool holder for storage of cleaning heads during use

Suction		
Voltage	V - Hz	110 / 230
Power	W	3000w
Amps	A	**110v:** 20 **230v:** 15
Max air flow	m^3/h / CFM	510 / 300
Noise level (EN ISO 3744)	dB(A)	67
Plug type	m^3/h / CFM	**110v:** 20amp **230v:** 15amp

Filter Unit		
Filter Type		Star
Surface - Diameter	cm^2-mm	500

Collection Unit		
Capacity	l	40
Inlet diameter		70mm

Volume		
Dimensions	cm	62 x 53 x 113h
Weight	kg	40
Tool Holders	✓	

SpaceVac™ INTERNATIONAL

spacevacinternational.com

Key Sectors:

- Retail ✓
- Education ✓
- Leisure & Tourism ✓
- Transport and Logistics ✓
- Manufacturing ✓
- FM/BSC ✓
- Healthcare & Pharma ✓
- Energy & Construction ✓

Suitable for use in any building with external guttering and downpipes including: Schools, Colleges, Apartment buildings, Domestic properties, warehouses, churches, hotels, theme parks, Hospitals and more.

Suggested for use with

- External **Lite** 50mm/2”
- External **Classic** 50mm/2”
- **Universal** 50mm/2”
- External **Pro** 70mm/2.7”

*See catalogue or website for more information on individual systems

